



# Product Data Sheet

## Bracton DP1 – Beer Line Cleaner (Part one in two part mix)

*Bracton DP1 is used with Bracton DP2 as a brewery approved beer line cleaning chemical. Approved for "Zero Degree" cleaning with frozen fonts, Dp1 and DP2 together will consistently remove weekly build up from beer reticulation systems, leaving lines hygienically clean and free from bacteria that can cause bad tasting beer. Essential for naturally brewed beer.*

### Product Description:

Bracton DP1 is one part of a two-part brewery approved beer line cleaner. DP1, when used in conjunction with DP2 will remove build up and bacteria from all types of draught beer lines and systems. Approved for zero degree cleaning, DP1 (together with DP2) should be used as per instructions once a week.

### Ideal for use on:

- Commercial Draught Beer System
- Domestic Draught Beer Systems
- Taps and fittings as a soaking solution

### Characteristics:

- Brewery approved
- Highly effective
- Easily removes heavy build up
- Approved for "Zero Degree" cleaning

### Tools / Equipment

- Gloves (non Pervious)
- Goggles (non vented)
- Cleaning vessel
- Bracton Beer Line Cleaning System
- Bracton Test Papers

### Safety

When using Bracton DP1 follow the safety directions on the label and wear appropriate personal protective equipment. Never mix DP1 and DP2 together in concentrated form.

### Directions for use:

#### Hand Mixing

1. Mix 80mls of DP1 and 80mls of DP2 to every 5 litres of water (working solution). It is important to mix DP1 and DP2 separately into the water.
2. Pull working solution through the beer lines and soak for minimum 2 hour or over night for best results.
3. Flush solution from beer lines with clean water. Using Bracton Test Papers, check that all chemicals have been flushed from the beer lines.
4. Connect beer and continue service.

### Bracton Beer Line Cleaning System

Clean as per instructions. Ensure pick up tubes are in the drum, free of cracks and are weighted to the bottom of the drum.

### Pack Sizes:

3 x 5 Lt, 15 Lt drum, 24 Lt drum and as part of a 10 Lt, 20 Lt or Handy pack kit.

**Notes:** Brass fittings and fixtures should be avoided in all draught beer systems. These fittings corrode and can taint the flavour of beer. All brass fittings should be replaced with stainless steel 304/316 fittings. A full catalogue of replacement fittings is available online at [www.bracton.com](http://www.bracton.com) or please call the numbers below.

#### Disclaimer

To the best of our knowledge and belief, the information is true and accurate at the time of publication. Since the conditions of use are out of the agents / distributors / manufacturers control, the end user must satisfy themselves by prior testing the product is suitable for their specific application.

Bracton Industries (NSW) Pty Limited  
Postal: PO Box 386, Brookvale NSW 2100 Australia  
Phone: (+612) 9938 1800  
Fax: (+612) 9905 0979  
Email: [sales@bracton.com](mailto:sales@bracton.com)  
Web: [www.bracton.com](http://www.bracton.com)