







### 3.2 Types of connections - B-lock / Pin & Line Valve

All metal beer connections which come into contact with beer are to be a minimum of 304 Grade Stainless Steel and any plastics are to be made from virgin material suitable for use food applications capable of withstanding highly alkaline environments. No brass or chrome plated metals are to be used.

TYPE	USE	IMAGE
<b>B-Lock 3/4 Adaptor</b>  <b>PART:SF2010</b>	Font adaptor. Used to allow removable taps for servicing or isolating a faulty tap.  Additional uses include beer manifolds & use in washout lines for cleaning of beer systems.	
<b>B-Lock 5/8 Adaptor</b>  <b>PART:SF2020</b>	Keg coupler adaptor used to allow quick connection of BLCV and Gas NRVs.  Facilitates rapid banking of kegs for peak periods. Predominantly used in VIC/SA/WA/NT/TAS	
<b>B-lock BLCV</b>  <b>PART: SF2120 (6mm) SF2130 (8mm) SF2140 (10mm) SF2150 (12mm)</b>	Used for connection on beer lines, to FOB/Beer pumps & on manifolds  Predominantly used in VIC/SA/WA/NT/TAS	
<b>Pin Valve 5/8 adaptor</b>  <b>PART:PF3020</b>	Keg coupler adaptor used to allow quick connection of beer & gas Line valves.  Facilitates rapid banking of kegs for peak periods.  Predominantly used in NSW/ACT/QLD	
<b>Line Valve</b>  <b>PART: PF3120 (6mm) PF3130 (8mm) PF3140 (10mm) PF3150 (12mm)</b>	Used for connection on beer lines, to FOB/Beer pumps & on manifolds  Predominantly used in NSW/ACT/QLD	